



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

PW

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/065,269	09/30/2002	Masahide Tanaka	106121.05	5680

25944 7590 05/02/2006

OLIFF & BERRIDGE, PLC  
P.O. BOX 19928  
ALEXANDRIA, VA 22320

EXAMINER
----------

HERNANDEZ, NELSON D

ART UNIT	PAPER NUMBER
----------	--------------

2622

DATE MAILED: 05/02/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

**Office Action Summary**

Application No.

10/065,269

Applicant(s)

TANAKA ET AL.

Examiner

Nelson D. Hernandez

Art Unit

2622

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --  
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 28 February 2006.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-27 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-27 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☒ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 28 February 2006 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some \* c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |  |   |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)   | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)   | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152)             |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)<br>Paper No(s)/Mail Date <u>1/31/2006</u> . | 6) <input type="checkbox"/> Other: _____  |

## **DETAILED ACTION**

### ***Response to Amendment***

1. The Examiner acknowledges the amended claims filed on February 28, 2006. Claims 1, 9-11 and 18 have been amended. Claims 24-27 have been newly added.

### ***Response to Arguments***

2. Applicant's arguments with respect to claims 1, 7, 10, 12-15 and 17-22 have been considered but are moot in view of the new ground(s) of rejection.

### ***Specification***

3. The amended title of the invention as filed on February 28, 2006 is not descriptive. A new title is required that is clearly indicative of the invention to which the claims are directed.

### ***Claim Objections***

4. **Claims 15 and 22** are objected to because of the following informalities: in claims 15 and 22, the limitation of "...a detector that detects a start of the transmission of the digital images" is not supported in the Specifications. The Examiner acknowledges that paragraph [0067] indicates that data can be transmitted automatically when the camera is placed on the docking station and that paragraphs [0096] – [0098] with Fig. 6 describes that communication between the camera on the

docking station and the image storage is detected. However, detecting a connection of the digital camera in the docking station and detecting communication (i.e. detecting types of files stored in the memory of the digital camera) is different from detecting a start of the transmission of the digital images as claimed. Therefore, the objection to these claims is maintained. For examining purposed the limitation in the claims will be read as "...a detector that detects a signal from the adapter to start the transmission of the digital images". Appropriate correction is required.

### ***Claim Rejections - 35 USC § 103***

5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

6. **Claims 1, 7, 10, 12-15, 17-22, 24 and 26 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chatani, JP 08-069684 A in view of Berstis, US Patent 6,721,001 B1.**

**Regarding claim 1**, Chatani discloses a digital image storage (Fig. 1) system comprising: a data storage (Fig. 1: 1) including a docking station (see fig. 1: 6) on which a digital camera (Fig. 1: 10) can be placed for transmitting images stored in a memory (Fig. 1: 8) of the digital camera to the docking station and for receiving electric power from the docking station to charge a battery (using battery charger in fig. 1: 9) of the digital camera, the data storage further including a storage medium (Fig. 1: 2) that

Art Unit: 2622

stores the transmitted digital images; and a controller (control circuit in fig. 2: 23) that controls the transmission of the digital images (Fig. 3, step S102) from the digital camera and the charging of the digital camera battery (Fig. 3, step S104) so that the charging and the transmission do not occur at the same time (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶ 0029).

Chatani does not explicitly disclose that the storage medium is disposed in a housing that is separate from a housing having the docking station.

However, Berstis teaches a discloses a digital image storage system comprising: a digital camera (Fig. 1: 102) having a memory (Fig. 2: 214) capable of storing digital images and a manually operable power switch (a power switch is inherently taught by Berstis; a data storage (Berstis teaches that the images are transmitted to a server or a computer system; col. 2, lines 40-46; col. 4, lines 53-63) having a storage medium (by teaching that the images are transmitted to a server or a computer system, Berstis inherently teaches a data storage having a storage medium for storing the digital images since a storage medium is necessitated to store the image data; col. 2, lines 40-46; col. 4, lines 53-63; a docking station (Fig. 1: 106) disposed on a housing separate from the housing where the storage medium is disposed (server or computer system) on which the digital camera can be placed to transmit the digital images stored in the memory of said camera to the storage medium in the data storage through said docking station; a controller (Fig. 2: 216) that controls the transmission of the digital images from the digital camera memory to the storage medium (Col. 1, lines 45-50; col. 2, line 15 – col. 3, line 8; col. 4, lines 29-63). Having the storage medium disposed in a housing

Art Unit: 2622

separate from the housing having the docking station is advantageous because it would allow the user to connect the digital camera to different data storages (i.e. pc, laptops, PDA's, etc), using the camera connected to the docking station as an external device that can be placed closer to the user for easy access offering the necessary support to secure the camera in place, reducing the amount of parts and costs of the data storage.

Therefore, taking the combined teaching of Chatani in view of Berstis as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Chatani by having the storage medium disposed in a housing that is separate from a housing having the docking station. The motivation to do so would have been to improve the digital image storage by allowing the user to connect the digital camera to different data storages (i.e. pc, laptops, PDA's, etc), using the camera connected to the docking station as an external device that can be placed closer to the user for easy access offering the necessary support to secure the camera in place, reducing the amount of parts and costs of the data storage.

**Regarding claim 7**, Chatani discloses that the docking station has an indicator (display shown in fig. 1: 3) that indicates information relevant to the charge to the battery (see translation, page 7, ¶ 0030).

**Regarding claim 10**, Chatani discloses a system for use with digital images, comprising: a docking station (see fig. 1: 6) on which a digital camera (Fig. 1: 10) can be placed for transmitting digital images stored in a memory (Fig. 1: 8) of the digital camera to the docking station and for receiving electric power to charge a battery of the digital camera (using battery charger in fig. 1: 9) while the digital camera is placed on the

docking station; and a controller (control circuit in fig. 2: 23) that controls the transmission of the digital images (Fig. 3, step S102) from the digital camera and the charging of the digital camera battery (Fig. 3, step S104) so that the charging and the transmission do not occur at the same time (transmission and charging occur at different steps; see fig. 3) (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029).

Chatani does not explicitly disclose the docking station transmitting the digital images from the digital camera to an external data storage that includes a housing that is separate from a housing having the docking station.

However, Berstis teaches a discloses a digital image storage system comprising: a digital camera (Fig. 1: 102) having a memory (Fig. 2: 214) capable of storing digital images and a manually operable power switch (a power switch is inherently taught by Berstis; a data storage (Berstis teaches that the images are transmitted to a server or a computer system; col. 2, lines 40-46; col. 4, lines 53-63) having a storage medium (by teaching that the images are transmitted to a server or a computer system, Berstis inherently teaches a data storage having a storage medium for storing the digital images since a storage medium is necessitated to store the image data; col. 2, lines 40-46; col. 4, lines 53-63; a docking station (Fig. 1: 106) disposed on a housing separate from the housing where the storage medium is disposed (server or computer system) on which the digital camera can be placed to transmit the digital images stored in the memory of said camera to the storage medium in the data storage through said docking station; a controller (Fig. 2: 216) that controls the transmission of the digital images from the digital camera memory to the storage medium (Col. 1, lines 45-50; col. 2, line 15 –

Art Unit: 2622

col. 3, line 8; col. 4, lines 29-63). Having the storage medium disposed in a housing separate from the housing having the docking station is advantageous because it would allow the user to connect the digital camera to different data storages (i.e. pc, laptops, PDA's, etc), using the camera connected to the docking station as an external device that can be placed closer to the user for easy access offering the necessary support to secure the camera in place, reducing the amount of parts and costs of the data storage.

Therefore, taking the combined teaching of Chatani in view of Berstis as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Chatani by having the docking station transmitting the digital images from the digital camera to an external data storage that includes a housing that is separate from a housing having the docking station. The motivation to do so would have been to improve the digital image storage by allowing the user to connect the digital camera to different data storages (i.e. pc, laptops, PDA's, etc), using the camera connected to the docking station as an external device that can be placed closer to the user for easy access offering the necessary support to secure the camera in place, reducing the amount of parts and costs of the data storage.

**Regarding claim 12**, Chatani discloses that the controller controls the transmission of the digital images and the charging of the battery so that the charging of the battery is started after the transmission of the digital images is stopped (as shown in fig. 4, the transmission of images occur in step S102 and the charging of the battery occur in step S104) (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029).



**Regarding claim 13**, Chatani discloses that the controller automatically starts the charging of the battery after the transmission of the digital images is stopped (as shown in fig. 4, the transmission of images occur in step S102 and the charging of the battery occur in step S104) (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029).

**Regarding claim 14**, Chatani inherently discloses that the controller starts the charging of the battery after a predetermined period of time has passed after the transmission of the digital images is stopped by teaching that the transmission of images occur in step S102 and the charging of the battery occur in step S104 (see fig. 4), since the transmission and charging of battery occur at different steps, it is expected to have a predetermined amount of time since the transmission is stopped to start charging the battery. Grounds for rejecting claim 1 apply here.

**Regarding claim 15**, Chatani discloses a detector that detects a signal from the adapter to start the transmission of the digital images (See translation, page 6, ¶ 0023 – page 7, ¶ 0030).

**Regarding claim 17**, Chatani discloses a digital camera (Fig. 1: 10) having a battery and a memory (Fig. 1: 8) capable of storing digital images (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029).

**Regarding claim 18**, the combined teaching of Chatani in view of Berstis as applied to claim 10 teaches a storage medium (See Chatani, fig. 1: 2) that stores the transmitted digital images from the digital camera memory through the docking station (See Chatani translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029), the storage medium

Art Unit: 2622

is disposed in the external data storage (See Berstis, col. 1, lines 45-50; col. 2, line 15 – col. 3, line 8; col. 4, lines 29-63). Grounds for rejecting claim 10 apply here.

**Regarding claim 19**, Chatani discloses that the controller controls the transmission of the digital images and the charging of the battery so that the charging of the battery is started after the transmission of the digital images is stopped (as shown in fig. 4, the transmission of images occur in step S102 and the charging of the battery occur in step S104) (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029).

**Regarding claim 20**, Chatani discloses that the controller automatically starts the charging of the battery after the transmission of the digital images is stopped (as shown in fig. 4, the transmission of images occur in step S102 and the charging of the battery occur in step S104) (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029).

**Regarding claim 21**, Chatani discloses that the controller starts the charging of the battery after a predetermined period of time has passed after the transmission of the digital images is stopped (as shown in fig. 4, the transmission of images occur in step S102 and the charging of the battery occur in step S104) (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029).

**Regarding claim 22**, Chatani discloses that the controller automatically starts the charging of the battery after the transmission of the digital images is stopped (as shown in fig. 4, the transmission of images occur in step S102 and the charging of the battery occur in step S104) (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029).

**Regarding claim 24**, the combined teaching of Chatani in view of Berstis as applied to claim 1 teaches the housing having the docking station does not include any

Art Unit: 2622

memory for storing the digital images (See Berstis Fig. 1; col. 1, lines 45-50; col. 2, line 15 – col. 3, line 8; col. 4, lines 29-63).

**Regarding claim 26**, the combined teaching of Chatani in view of Berstis as applied to claim 10 teaches the housing having the docking station does not include any memory for storing the digital images (See Berstis Fig. 1; col. 1, lines 45-50; col. 2, line 15 – col. 3, line 8; col. 4, lines 29-63).

**7. Claims 2-5 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chatani, JP 08-069684 A in view of Berstis, US Patent 6,721,001 B1 and further in view of Dowe, US Patent 5,602,458.**

**Regarding claim 2**, the combined teaching of Chatani in view of Berstis fails to teach that the digital camera including a manually operable power switch that switches the digital camera between an operative state and an inoperative state.

However, Dowe teaches a camera (Fig. 3: 110) comprising a power switch (Fig. 1: 16) that switches the digital camera between an operative state and an inoperative state (Col. 2, line 65 – col. 3, line 14). It is advantageous to have the camera comprising a power switch, so the camera can be turn off when is not needed to pickup images in order to increase the battery life of said camera.

Therefore, taking the combined teaching of Chatani in view of Berstis and further in view of Dowe as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the camera taught in Chatani and Berstis by having a power switch that switches the digital camera between an operative state

and an inoperative state. The motivation to do so would have been to improve the digital camera by increasing the battery life of said camera.

**Regarding claim 3**, the combined teaching of Chatani in view of Berstis fails to teach that the controller starts the charging of the digital camera battery regardless of the manual operation of the digital camera power switch between the operative state and the inoperative state.

However, Dowe teaches a camera (Fig. 3: 110) comprising a power switch (Fig. 1: 16) that switches the digital camera between an operative state and an inoperative state (Col. 2, line 65 – col. 3, line 14), said camera is connected to a charging cradle (Fig. 3: 112) in order to recharge the battery in said camera, wherein, when said camera is connected to said charging cradle, the charging cradle proceeds to charge the battery of said camera, regardless of the status of the power switch of said camera (Col. 2, lines 29-46; col. 3, lines 32-56; col. 4, lines 26-37; col. 5, lines 9-37). Charging of the digital camera battery regardless of the manual operation of the digital camera power switch is advantageous because would allow the camera to recharge the battery even if the camera power switch is mistakenly left in an on condition, ensuring that the battery will be recharged and ready for use.

Therefore, taking the combined teaching of Chatani in view of Dowe as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the camera in Chatani and Berstis by charging of the digital camera battery regardless of the manual operation of the digital camera power switch between the operative state and the inoperative state. The motivation to do so would have been

Art Unit: 2622

to recharge the battery even if the camera power switch is mistakenly left in an on condition, ensuring that the battery will be recharged and ready for use as suggested by Dowe (Col. 2, lines 39-46).

**Regarding claim 4**, limitations can be found in claim 2.

**Regarding claim 5**, the combined teaching of Chatani in view of Berstis and further in view of Dowe as applied to claim 4 teaches that the controller causes the digital camera to be switched from the operative state to the inoperative state before the controller causes the digital camera battery to be charged (See Dowe, col. 2, lines 29-46; col. 3, lines 31-56; col. 5, lines 9-28).

**8. Claim 6 is rejected under 35 U.S.C. 103(a) as being unpatentable over Chatani, JP 08-069684 A and Berstis, US Patent 6,721,001 B1 in view of Dowe, US Patent 5,602,458 and further in view of Takahashi, US Patent 6,580,460 B1.**

**Regarding claim 6**, the combined teaching of Chatani in view of Berstis and further in view of Dowe fails to teach that the controller switches the digital camera from the operative state to the inoperative state subsequent to completion of the transmission of the digital images.

However, Takahashi teaches a camera (Fig. 1: 117) connectable to a printer (Fig. 1: 118) for transmission of image data from said camera to said printer, wherein, when the transfer of image data from the camera to the printer is completed, said camera proceeds to turn off its power supply in order to reduce consumption of power (Col. 3, lines 29-42; col. 14, lines 19-25). Switching from an operative state to an

inoperative state after transmitting the digital images is advantageous because it would to reduce the power consumption of the digital camera.

Therefore, taking the combined teaching of Chatani and Berstis in view of Dowe and further in view of Takahashi as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the camera in Chatani, Berstis and Dowe by switching the digital camera from the operative state to the inoperative state subsequent to completion of the transmission of the digital images. The motivation to do so would have been to reduce would to reduce the power consumption of the digital camera as suggested by Takahashi (Col. 14, lines 19-25).

**9. Claim 8 is rejected under 35 U.S.C. 103(a) as being unpatentable over Chatani, JP 08-069684 A in view of Berstis, US Patent 6,721,001 B1 and further in view of Ramsier, US Patent 5,844,400.**

**Regarding claim 8**, the combined teaching of Chatani in view of Berstis fails to teach a battery detector that detects a kind of battery within the digital camera.

However, detecting a kind of battery of an electronic device connected to a docking station is notoriously well known in the art as taught by Ramsier, who teaches a mobile terminal (Fig. 2: 10) is connectable to a cradle (Fig. 2: 90), wherein said cradle comprises a processor (Fig. 4: 200), which is able to discriminate among different battery types being used in the mobile terminal when said mobile terminal is connected to said cradle, the cradle determines the type of battery (Col. 2, lines 8-52; col. 5, lines 36-65; col. 7, line 47 – col. 8, line 11; col. 8, lines 25-62). Although the electronic device in Ramsier is a mobile telephone and not a camera, Ramsier teaches that the concept

Art Unit: 2622

may be applied to any other electronic portable device, which employs rechargeable batteries (Col. 4, lines 15-38). Detecting the type of battery of the electronic device connected to the docking station is advantageous because it would increase the versatility in the use various types of batteries in the camera since one battery charger may be employed to charge the various typed of batteries that may be used.

Therefore, taking the combined teaching of Chatani in view of Berstis and further in view of Ramsier as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the docking station in Chatani and Berstis to discriminate a kind of battery being used in the camera. The motivation to do so would have been to increase the versatility in the use various types of batteries in the camera since one battery charger may be employed to charge the various typed of batteries that may be used as suggested by Ramsier (Col. 2, lines 8-21).

**10. Claims 9, 11, 25 and 27 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chatani, JP 08-069684 A in view of Berstis, US Patent 6,721,001 B1 and further in view of Takahashi, US Patent 6,580,460 B1.**

**Regarding claim 9**, Chatani discloses a digital image storage system (Fig. 1) comprising: a digital camera (Fig. 1: 10) having a memory (Fig. 1: 8) capable of storing digital images; a data storage (Fig. 1: 1) including a docking station (Fig. 1: 6) on which the digital camera can be laid for transmitting the digital images of the digital camera memory to the docking station, a storage medium (Fig. 1: 2) that stores the digital images transmitted from the digital camera memory from the docking station; and a controller (control circuit in fig. 2: 23) that receives a signal from the docking station to

Art Unit: 2622

receive the transmission of the digital images (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029).

Chatani fails to teach that the storage medium is disposed in a housing that is separate from a housing having the docking station and a manually operable power switch that switches the digital camera between an operative state and an inoperative state and that after the digital images transmission is terminated, the controller automatically causes a switching of the digital camera from the operative state to the inoperative state without the manual operation of the power switch.

However, Berstis teaches a discloses a digital image storage system comprising: a digital camera (Fig. 1: 102) having a memory (Fig. 2: 214) capable of storing digital images and a manually operable power switch (a power switch is inherently taught by Berstis; a data storage (Berstis teaches that the images are transmitted to a server or a computer system; col. 2, lines 40-46; col. 4, lines 53-63) having a storage medium (by teaching that the images are transmitted to a server or a computer system, Berstis inherently teaches a data storage having a storage medium for storing the digital images since a storage medium is necessitated to store the image data; col. 2, lines 40-46; col. 4, lines 53-63; a docking station (Fig. 1: 106) disposed on a housing separate from the housing where the storage medium is disposed (server or computer system) on which the digital camera can be placed to transmit the digital images stored in the memory of said camera to the storage medium in the data storage through said docking station; a controller (Fig. 2: 216) that controls the transmission of the digital images from the digital camera memory to the storage medium (Col. 1, lines 45-50; col. 2, line 15 –



Art Unit: 2622

col. 3, line 8; col. 4, lines 29-63). Having the storage medium disposed in a housing separate from the housing having the docking station is advantageous because it would allow the user to connect the digital camera to different data storages (i.e. pc, laptops, PDA's, etc), using the camera connected to the docking station as an external device that can be placed closer to the user for easy access offering the necessary support to secure the camera in place, reducing the amount of parts and costs of the data storage.

Therefore, taking the combined teaching of Chatani in view of Berstis as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Chatani by having the docking station transmitting the digital images from the digital camera to an external data storage that includes a housing that is separate from a housing having the docking station. The motivation to do so would have been to improve the digital image storage by allowing the user to connect the digital camera to different data storages (i.e. pc, laptops, PDA's, etc), using the camera connected to the docking station as an external device that can be placed closer to the user for easy access offering the necessary support to secure the camera in place, reducing the amount of parts and costs of the data storage.

The combined teaching of Chatani in view of Berstis fails to teach a manually operable power switch that switches the digital camera between an operative state and an inoperative state and that after the digital images transmission is terminated, the controller automatically causes a switching of the digital camera from the operative state to the inoperative state without the manual operation of the power switch.

However, Takahashi teaches a camera (Fig. 1: 117) connectable to a printer (Fig. 1: 118) for transmission of image data from said camera to said printer, the camera comprising a power switch that switches the digital camera between an operative state and an inoperative state (Col. 12, line 63 – col. 13, line 36), wherein, when the transfer of image data from the camera to the printer is completed, said camera proceeds to turn off its power supply in order to reduce consumption of power (Col. 3, lines 29-42; col. 14, lines 19-25). Switching from an operative state to an inoperative state after transmitting the digital images is advantageous because it would reduce the power consumption of the digital camera.

Therefore, taking the combined teaching of Chatani in view of Berstis and further in view of Takahashi as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the camera in Chatani and Berstis by switching the digital camera from the operative state to the inoperative state subsequent to completion of the transmission of the digital images. The motivation to do so would have been to reduce the power consumption of the digital camera as suggested by Takahashi (Col. 14, lines 19-25).

**Regarding claim 11**, Chatani discloses a digital image storage system comprising: a digital camera (Fig. 1: 10) having a memory (Fig. 1: 8) capable of storing digital images; a docking station (Fig. 1: 6) on which a digital camera can be placed for transmitting the digital images of the digital camera memory to the docking station; a storage medium (Fig. 1: 2) that stores the digital images transmitted from the digital camera through the docking station; and a controller (control circuit in fig. 2: 23) that

Art Unit: 2622

receives a signal from the docking station to receive the transmission of the digital images (See translation, page 6, ¶ 0019, ¶ 0023 – page 7, ¶0029)

Chatani fails to teach the docking station transmitting the digital images from the digital camera to an external data storage that includes a housing that is separate from a housing having the docking station and a manually operable power switch that switches the digital camera between an operative state and an inoperative state and that after the digital images transmission is terminated, the controller automatically causes a switching of the digital camera from the operative state to the inoperative state without the manual operation of the power switch.

However, Berstis teaches a discloses a digital image storage system comprising: a digital camera (Fig. 1: 102) having a memory (Fig. 2: 214) capable of storing digital images and a manually operable power switch (a power switch is inherently taught by Berstis; a data storage (Berstis teaches that the images are transmitted to a server or a computer system; col. 2, lines 40-46; col. 4, lines 53-63) having a storage medium (by teaching that the images are transmitted to a server or a computer system, Berstis inherently teaches a data storage having a storage medium for storing the digital images since a storage medium is necessitated to store the image data; col. 2, lines 40-46; col. 4, lines 53-63; a docking station (Fig. 1: 106) disposed on a housing separate from the housing where the storage medium is disposed (server or computer system) on which the digital camera can be placed to transmit the digital images stored in the memory of said camera to the storage medium in the data storage through said docking station; a controller (Fig. 2: 216) that controls the transmission of the digital images from

Art Unit: 2622

the digital camera memory to the storage medium (Col. 1, lines 45-50; col. 2, line 15 – col. 3, line 8; col. 4, lines 29-63). Having the storage medium disposed in a housing separate from the housing having the docking station is advantageous because it would allow the user to connect the digital camera to different data storages (i.e. pc, laptops, PDA's, etc), using the camera connected to the docking station as an external device that can be placed closer to the user for easy access offering the necessary support to secure the camera in place, reducing the amount of parts and costs of the data storage.

Therefore, taking the combined teaching of Chatani in view of Berstis as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Chatani by having the docking station transmitting the digital images from the digital camera to an external data storage that includes a housing that is separate from a housing having the docking station. The motivation to do so would have been to improve the digital image storage by allowing the user to connect the digital camera to different data storages (i.e. pc, laptops, PDA's, etc), using the camera connected to the docking station as an external device that can be placed closer to the user for easy access offering the necessary support to secure the camera in place, reducing the amount of parts and costs of the data storage.

The combined teaching of Chatani in view of Berstis fails to teach a manually operable power switch that switches the digital camera between an operative state and an inoperative state and that after the digital images transmission is terminated, the controller automatically causes a switching of the digital camera from the operative state to the inoperative state without the manual operation of the power switch.

However, Takahashi teaches a camera (Fig. 1: 117) connectable to a printer (Fig. 1: 118) for transmission of image data from said camera to said printer, the camera comprising a power switch that switches the digital camera between an operative state and an inoperative state (Col. 12, line 63 – col. 13, line 36), wherein, when the transfer of image data from the camera to the printer is completed, said camera proceeds to turn of its power supply in order to reduce consumption of power (Col. 3, lines 29-42; col. 14, lines 19-25). Switching from an operative state to an inoperative state after transmitting the digital images is advantageous because it would to reduce the power consumption of the digital camera.

Therefore, taking the combined teaching of Chatani in view of Berstis and further in view of Takahashi as a whole, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the camera in Chatani and Berstis by switching the digital camera from the operative state to the inoperative state subsequent to completion of the transmission of the digital images. The motivation to do so would have been to reduce the power consumption of the digital camera as suggested by Takahashi (Col. 14, lines 19-25).

**Regarding claim 25**, the combined teaching of Chatani in view of Berstis and further in view of Takahashi as applied to claim 9 teaches the housing having the docking station does not include any memory for storing the digital images (See Berstis Fig. 1; col. 1, lines 45-50; col. 2, line 15 – col. 3, line 8; col. 4, lines 29-63).

**Regarding claim 27**, the combined teaching of Chatani in view of Berstis and further in view of Takahashi as applied to claim 11 teaches the housing having the

Art Unit: 2622

docking station does not include any memory for storing the digital images (See Berstis Fig. 1; col. 1, lines 45-50; col. 2, line 15 – col. 3, line 8; col. 4, lines 29-63).

**11. Claims 16 and 23 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chatani, JP 08-069684 A in view of Berstis, US Patent 6,721,001 B1 and further in view of Asakawa, US Patent 6,135,809.**

**Regarding claim 16**, the combined teaching of Chatani in view of Berstis fails to teach that the detector includes a mechanical contact and a sensor.

However, using a mechanical connector and a sensor for detecting the connection of an electronic device to another is well known in the art as taught by Asakawa. Asakawa teaches a card connector (Figs. 3 and 5A-5C) having electrical contacts (Fig. 3, items 20 and 52) forming electrical connections with a memory card (Figs. 5A-5C, item C) inserted therein and detecting or sensing unit including a set of sensing members connected to a detecting circuit indicating the state when the card is fully inserted into the connector, and one of the sensing members (Fig. 3, items 20-20c, 52 and 54) has a bend that exerts pressure on one surface of the card in a perpendicular direction relative to the one surface and closes or opens the detecting circuit (See figs. 3 and 5; col. 1, lines 57-65; col. 2, line 59 – col. 3, line 39). Having the detector including a mechanical contact and a sensor is advantageous because it would help determining whether the camera is properly connected to the image storage, providing reliable electrical connection between the devices.

Therefore, taking the combined teaching of Chatani in view of Berstis and further in view of Asakawa as a whole, it would have been obvious to one of ordinary skilled in

Art Unit: 2622

the art at the time the invention was made to modify the connection means in Chatani and Berstis by including sensing members connected to the detecting circuit to determine if the connection means for connecting the camera and the image storage is fully inserted. The motivation to do so would have been so would help the image storage to determine whether the camera is properly connected to the image storage, providing reliable electrical connection between the devices as suggested in Asakawa (Col. 1, lines 46-51).

**Regarding claim 23**, the combined teaching of Chatani in view of Berstis fails to teach that the detector includes a mechanical contact and a sensor.

However, using a mechanical connector and a sensor for detecting the connection of an electronic device to another is well known in the art as taught by Asakawa. Asakawa teaches a card connector (Figs. 3 and 5A-5C) having electrical contacts (Fig. 3, items 20 and 52) forming electrical connections with a memory card (Figs. 5A-5C, item C) inserted therein and detecting or sensing unit including a set of sensing members connected to a detecting circuit indicating the state when the card is fully inserted into the connector, and one of the sensing members (Fig. 3, items 20-20c, 52 and 54) has a bend that exerts pressure on one surface of the card in a perpendicular direction relative to the one surface and closes or opens the detecting circuit (See figs. 3 and 5; col. 1, lines 57-65; col. 2, line 59 – col. 3, line 39). Having the detector including a mechanical contact and a sensor is advantageous because it would help determining whether the camera is properly connected to the image storage, providing reliable electrical connection between the devices.

Therefore, taking the combined teaching of Chatani in view of Berstis and further in view of Asakawa as a whole, it would have been obvious to one of ordinary skilled in the art at the time the invention was made to modify the connection means in Chatani and Berstis by including sensing members connected to the detecting circuit to determine if the connection means for connecting the camera and the image storage is fully inserted. The motivation to do so would have been so would help the image storage to determine whether the camera is properly connected to the image storage, providing reliable electrical connection between the devices as suggested in Asakawa (Col. 1, lines 46-51).

### ***Conclusion***

12. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of



Art Unit: 2622

the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

**Contact**

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Nelson D. Hernandez whose telephone number is (571) 272-7311. The examiner can normally be reached on 8:30 A.M. to 6:00 P.M..

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Ometz can be reached on (571) 272-7593. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

NDHH  
April 26, 2006

  
TUAN HO  
PRIMARY EXAMINER

Nelson D. Hernandez  
Examiner  
Art Unit 2622